

**LIGHT IT UP.** Anywhere you want.



**IllumiSign™ from Sol**

On or off the grid.

Your message. Your choice.

**Sol**® 

Reliable. Renewable. Remarkable.



## **IllumiSign™ LED backlit sign solution** **The better, brighter light bar**

### **UNIFORM LED BRILLIANCE**

Compared with fluorescent tubes, IllumiSign's LED design eliminates hot spots, improves visibility and offers a level of durability that's as good as it gets.

### **EASY TO INSTALL**

Other lighting products require lengthy, costly electrical wiring in the shop when the sign box is built. Sol's IllumiSign™ LED systems are strictly plug-and-play, with no additional wiring required. You save on labor and assembly costs.

### **ENERGY EFFICIENT**

IllumiSign™ uses as little as 10% of the electricity of conventional lighting, providing significant operational savings.

### **MAINTENANCE FREE**

Compared with conventional lighting, the savings on maintenance alone can pay for the Sol IllumiSign™.

### **THE EXCLUSIVE SOLAR OPTION**

Only Sol offers the incredible flexibility of solar power, allowing IllumiSign™ systems to be installed off the grid, whether that's desired or required. Brilliant illumination and reliable performance—wherever you need it. No electricity? No problem!

### **BUILT TO ENDURE**

IllumiSign™ is ETL listed to the UL 48 standard, is made with a rugged aluminum housing and provides a service life of 100,000 hours—that's at least 15 years of brilliant illumination. Best of all, IllumiSign™ carries an industry leading 5-year warranty, thanks to proven reliability.



Reliable. Renewable. Remarkable.

Sol Inc. | Palm City, Florida | 772.286.9461  
info@solarlighting.com | www.solarlighting.com

**IllumiSign™ signage systems from Sol**  
On or off the grid. Your message. Your choice.



## IllumiSign™ LED backlit sign solution

The better, brighter light bar

### FEATURES

- Uniform brilliance with the highest luminous efficacy
- Cost effective light source compared to fluorescent
- Built to endure with superior reliability
- Extremely long life span
- Exclusive solar option
- Easy-to-install



### SPECIFICATIONS

voltage, nominal	25 VDC
current	1.65 A
voltage, max	26 VDC
range	1.25-2.55A @ 24VDC
light color temperature	6500 K
lightsource	Sol's LED Uni-light
life span	100,000 hours
operating temperature	-20 F to +120 F
storage temperature	-40 F to +180 F
operating humidity, non-condensing	100%
storage humidity, non-condensing	100%
dimensions, L (including mounting) x H x D	45.1" x 2" x 2"
packaging	Aluminum Housing
weight	3.5 Lbs



Reliable. Renewable. Remarkable.

Sol Inc. | Palm City, Florida | 772.286.9461  
 info@solarlighting.com | www.solarlighting.com

**IllumiSign™ signage systems from Sol**  
 On or off the grid. Your message. Your choice.

0308 MRKT-ILLUMSIGN-002