

Metro LED Luminaire

FEATURES

This luminaire is designed for outdoor lighting applications.

Powered by a solar power collection array, an ideal fixture for residential roadways, walkways, pathways, parks, trails and parking lots.

SPECIFICATIONS

Heavy duty one piece cast aluminum housing

Standard finish is electrostatic baked acrylic paint.

Standard colors: park green, black, bronze and white.

Other colors available.

Arm is 48" davit arm designed to mount to 4" OD pole.

Can be installed in less than an hour, and can be placed in virtually any location that isn't shaded.

DATA

Light Output:

- Solid state strip type LED
- Light color: 5100 K
- CRI Index 80
- LED pack produces rectangular light pattern
- Lamp rated wattage: up to 22 Watts
- Programmable all night with dimming capabilities
- LED rating: 70,000 hours (L-70)

Fixture:

- Heavy duty cast aluminum housing
- Power-coated paint finish
- Condensation prevention
- Dimensions: 20" high x 27" diameter
- Weight: 6 lbs.

Support Arm:

- Length: 48" davit arm
- Grade "A" corrosion resistant aluminum
- Weight: 17 lbs.

Battery Box:

- ESA 100 to ESA 400
- Grade "A" corrosion resistant aluminum

Battery:

- 100 AH gel cell – no maintenance
- 100 amp hour resistant
- Weight: 62 lbs.



Sol[®]
Reliable. Renewable. Remarkable.

rev. 0410 MRKT-METROLED-001