

Solar LED Transit Shelter Advertising Light (TSAL)

The better brighter light bar for shelter signs

IMPROVES SECURITY

- Bright white LEDs illuminate advertising inside and/or outside transit shelter all night long.
- Provided greater security and comfort for commuters.

UNIFORM LED BRILLIANCE

- Remarkable LED technology provides efficient, bright and aesthetically pleasing light.
- LEDs rated at 70,000 hours (L-70) for 15+ years of brilliant illuminations.

NO POWER? NO PROBLEM.

- Installs where no power source exists.
- 5 nights battery backup during inclement weather.

EASY TO INSTALL

- Save on labor and assembly costs.
- No trenching, meters, wiring, or utility headaches.
- LED systems are strictly plug-and-play.
- Easy to in install (less than an hour) or relocate.



ENERGY EFFICIENT AND SUSTAINABLE

- SOL's LED technology uses up to 50% less energy compared to conventional lighting
- Saves you money and helps the environment.
- Unlike conventional lights, no risk of hazardous disposal – CF, CCFL, LPS and HPS contain mercury.

BUILT TO ENDURE AND VANDAL RESISTANT

- Modular design.
- Built with sturdy, corrosive-resistant aluminum.
- FivePlus™ Warranty includes 10 years on electronics, wiring, fixtures and 20 years on mounting hardware and solar panels.
- National Electric Code Article 690 Compliant.

Sol[®]
Reliable. Renewable. Remarkable.

Solar LED Transit Shelter Advertising Light (TSAL)

The better brighter light bar for shelter signs



SPECIFICATIONS

System voltage	12V DC
Solar power array*	80 to 250 watts
Batteries	12V 100 Ah NRGLife™gel cell maintenance-free
Battery reserve	5 day autonomy
Light color temperature	6500 K
Light source	SOL's LED UniLight
LED life span	70,000 hours (L-70)
Operating temperature	-20 F to +120 F
Storage temperature	-40 F to +180 F
Operating humidity, non-condensing	100%
Storage humidity, non-condensing	100%
Operating hours	Programmable, 6 hrs to dusk to dawn
Dimensions, L (including mounting) x H x D	45.1" x 2" x 2" (back-to-back) 69" x 2" x 2" (V-box)
Enclosure	Aluminum
Weight	3.5 lbs

*Solar panel specifications may vary by manufacturer and system size will vary with location.



Sol® 
Reliable. Renewable. Remarkable.

rev 0410 MRKT-TSAL-001